



IFW

In re Application of: Miele

Art Unit: 1711

Serial No. 10/647917

Case Docket No. 7170

Filed: August 26, 2003

Examiner:

For: Low Emission Fibrous Webs and Method of Making

I hereby certify that this correspondence is being deposited
with the United States Postal Service as first class mail in an
envelope addressed to: Commissioner of Patents and
Trademarks, Washington, D.C. 20231 on 8-10-04

Commissioner of the Patents & Trademarks
Washington, D. C. 20231

JOHN MANVILLE INTERNATIONAL, INC.
John Manville
8-10-04
Date

Dear Sir:

Information Disclosure Statement

The following references are known to the Applicant and Applicant's attorney.
These references involve low formaldehyde compositions.

1. United States Pat. No. 5,143,954 teaches a low formaldehyde, self-cross linking polymer latex composition for use in making nonwoven products, the composition including one or more very complex and costly formaldehyde scavengers such as N-hydroxyethylethyleneurea, ethyl acetoacetate, 2,4-pentanedione, esters of 2-cyanoacetate, 2-cyanoacetamide, trimethylopropane tricyanoacetate, and the polymerized residue of methacryloxyethyleneurea.
2. United States Pat. No. 5,160,679 teaches using acetoacetamide as an effective formaldehyde scavenger in the manufacture of wood particleboard and durable press finished fabrics that use urea formaldehyde as a binder.
3. United States Pat. No. 5,446,195 teaches formaldehyde scavengers widely used in durable press finishing compositions and wood particleboard such as diethylene glycol, sorbitol, urea, melamine, diazine, triazine, and a water-soluble active methylene compound.
4. United States Pat. No. 5,578,371 teaches adding urea, melamine, dicyandiamide and/ or 1-10 wt. percent of a water-soluble bisulfite or precursor to urea extended phenol

formaldehyde binders in the manufacture of fiber glass insulation products, which products are not later coated or impregnated with hot asphalt.

5. United States Pat. No. 5,612,405 teaches glass fiber products bonded with a binder containing an aqueous compatible formaldehyde resin like phenolic resin, an aqueous latex elastomeric polymer like styrene butadiene, ethylene propylene monomer, ethylene propylene-diene terpolymer, etc., an acrylic polymer like copolymers of acrylic acid, methacrylic acid acrylic or methacrylic acid esters from 1-4 carbon atoms, acrylamide polymers or copolymers and esters thereof of from 1-4 carbon atoms, and a formaldehyde scavenger like melamine, guanamine, benzyl guanamine, guanidine, dicyandiamide, and the like.


6. United States Pat. No. 5,719,228 teaches using furan resins to bond glass fibers together to manufacture glass fiber products and to add urea or ammonia as formaldehyde scavengers, but also teach that these known additives produce disadvantages and therefore prefer to prereact an acidic furan resin, a formaldehyde scavenger and a source of reactable formaldehyde with a source of ammonia before spraying the binder onto the glass fibers.

7. United States Patent No. 5,795,933 teaches aqueous metal coating compositions comprising a formaldehyde containing resin and a formaldehyde scavenger consisting essentially of an organic compound having at least one active methylene hydrogen and a pKa about 5 to 13.

Respectfully submitted,


Attorney for Applicants

Robert D. Touslee
Registration No. 34,032
303-978-3927



INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Use as many sheets as necessary)

Sheet

of

Application Number	10/647917
Filing Date	8/26/03
First Named Inventor	Miele
Art Unit	1711
Examiner Name	
Attorney Docket Number	7179

[illegible][illegible]

Examiner
Signature

Date
Considered

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. ¹Applicant's unique citation designation number (optional). ²See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. ³Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). ⁴For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. ⁵Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. ⁶Applicant is to place a check mark here if English language Translation is attached.

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 (1-800-786-9199) and select option 2.